NSN 5306-01-364-3565

Shear Bolt - Page 1 of 2

Thread Class:





3a **Thread Direction: Right-hand Thread Length:** 1.005 inches Fastener Length: Between 3.880 inches and 3.910 inches **Head Style:** Spline extended washer **Head Height:** Between 0.552 inches and 0.572 inches **Extended Washer Diameter:** Between 1.153 inches and 1.163 inches **Extended Washer Thickness:** Between 0.080 inches and 0.100 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches Head Minor Diameter: Between 0.673 inches and 0.688 inches **Thread Diameter:** 0.625 inches Grip Length: Between 2.865 inches and 2.885 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 48.0 rockwell c and 50.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 ty2 cl2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5306-01-364-3565

Shear Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

