

View Online at <https://aerobasegroup.com/nsn/5306-01-364-3572>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.454 inches

Fastener Length:

Between 1.564 inches and 1.594 inches

Head Style:

Hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches bearing surface of head and 0.116 inches bearing surface of head

Thread Diameter:

0.375 inches

Grip Length:

Between 1.115 inches and 1.135 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.448 inches grip and 1.488 inches grip

Surface Finish:

32.0 microinches bearing surface of head

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response and ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Thread Series Designator:

Unjf

Specification Data:

80205-nas6406 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0