## NSN 5306-01-364-4809

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-364-4809

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.836 inches
Fastener Length:
Between 2.098 inches and 3.128 inches
Head Style:
Spline extended washer
Head Height:
Between 0.440 inches and 0.460 inches
Extended Washer Diameter:
Between 0.922 inches and 0.932 inches
Extended Washer Thickness:
Between 0.032 inches and 0.062 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Head Minor Diameter:
Between 0.547 inches and 0.562 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 2.240 inches and 2.260 inches
Features Provided:
Dry film lubricant
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Surface Finish:
32.0 microinches primary washer32.0 microinches grip
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response or ams5663 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification 1st treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-364-4809

Shear Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0