## NSN 5306-01-365-0350

Shear Bolt - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5306-01-365-0350

3a
Thread Direction:
Right-hand
Thread Length:
0.345 inches
Fastener Length:
Between 0.768 inches and 0.798 inches
Head Style:
Dished hexagon
Head Height:
Between 0.110 inches and 0.125 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.428 inches and 0.448 inches
Features Provided:
Dry film lubricant
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Product Name:
Navy special project
Special Features:
Dry film lubricant per mil-l-8937
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-365-0350

Shear Bolt - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0