

View Online at <https://aerobasegroup.com/nsn/5306-01-365-1764>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.300 inches

Fastener Length:

Between 0.887 inches and 0.892 inches

Head Style:

Hexagon

Head Height:

Between 0.108 inches and 0.113 inches

Width Between Flats:

Between 0.339 inches and 0.344 inches

Shoulder Diameter:

0.247 inches first shoulder and 0.249 inches first shoulder

Shoulder Length:

0.327 inches first shoulder

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Shoulder Shape:

Round first shoulder

Material:

Steel comp xm-12

Material Specification:

Ams 5659 h1100 assn standard single material response

Surface Treatment:

Primer sides of head and plastic polyurethane sides of head primer top of head and plastic polyurethane top of head

Surface Treatment Specification:

Mil-c-8514 military specification 1st treatment response sides of head and mil-p-23377 type 1 military specification 1st treatment response sides of head and mil-c-83286 military specification 2nd treatment response sides of head mil-c-8514 military specification 1st treatment response top of head and mil-p-23377 type 1 military specification 1st treatment response top of head and mil-c-83286 military specification 2nd treatment response top of head

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8514 spec.