

View Online at <https://aerobasegroup.com/nsn/5306-01-365-1765>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.240 inches

**Fastener Length:**

0.760 inches

**Head Style:**

Hexagon

**Head Height:**

0.026 inches

**Width Between Flats:**

Between 0.679 inches and 0.688 inches

**Hole Diameter:**

0.059 inches

**First Diameter From Head:**

Between 0.4365 inches and 0.4370 inches

**Second Diameter From Head:**

Between 0.309 inches and 0.315 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.370 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.120 inches

**Thread Diameter:**

0.375 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

128000 pounds per square inch

**Hole Configuration Style:**

Hexagon corners

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 cond f military specification single material response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.