NSN 5306-01-365-1766

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-365-1766 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.024 inches **Fastener Length:** 0.760 inches **Head Style:** Hexagon **Head Height:** 0.220 inches Width Between Flats: Between 0.554 inches and 0.562 inches **Hole Diameter:** 0.059 inches First Diameter From Head: Between 0.3740 inches and 0.3745 inches **Second Diameter From Head:** Between 0.246 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.370 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.120 inches **Thread Diameter:** 0.312 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 128000 pounds per square inch **Hole Configuration Style:** Hexagon corners **Externally Relieved Body Diameter Quantity:** 1

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 cond f military specification single material response

NSN 5306-01-365-1766

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-s-6758 spec.