# NSN 5306-01-365-3162

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-365-3162

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:

0.688 inches

#### Fastener Length:

Between 0.989 inches and 1.019 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.125 inches and 0.135 inches

### Width Between Flats:

Between 0.430 inches and 0.439 inches

### Grip Diameter:

Between 0.2485 inches and 0.2495 inches

**Thread Diameter:** 

0.250 inches

# Grip Length:

Between 0.678 inches and 0.698 inches

# Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4340 or steel comp 8740

## **Material Specification:**

Mil-s-5000 military specification 1st material response and mil-s-6049 military specification 2nd material response

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response

## **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas1104-11 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# NSN 5306-01-365-3162

Shear Bolt - Page 2 of 2

**Fiig:** A003b0

Mil-std (military Standard):

Mil-s-5000 spec.

