NSN 5306-01-365-7255

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-365-7255

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.735 inches
Fastener Length:
Between 1.845 inches and 1.875 inches
Head Style:
Dished hexagon
Head Height:
Between 0.250 inches and 0.265 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
1.115 inches
Thready Qty Per Inch (tpi):
20
20
20 Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 160000 pounds per square inch
Min. Tensile Strength (psi): 160000 pounds per square inch Material:
Min. Tensile Strength (psi): 160000 pounds per square inch Material: Iron alloy 660
Min. Tensile Strength (psi): 160000 pounds per square inch Material: Iron alloy 660 Material Specification:
Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material response and ams 5731 assn standard single material response
 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response and ams 5731 assn standard single material response Surface Treatment:
 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response and ams 5731 assn standard single material response Surface Treatment: Passivate
Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material response and ams 5731 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:
Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material response and ams 5731 assn standard single material responseSurface Treatment:PassivateGurface Treatment Specification:Qq-p-35 federal specification single treatment response
Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material response and ams 5731 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:
Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material response and ams 5731 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:Unjf
Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material response and ams 5731 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseIntread Series Designator:UnjfSpecification Data:
Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Inon alloy 660Material Specification:Ams 5737 assn standard single material response and ams 5731 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UnifSpecification Data:80205-nas6708u18 professional/industrial association standard
Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Inon alloy 660Material Specification:Ams 5737 assn standard single material response and ams 5731 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:(q-p-35 federal specification single treatment response)Thread Series Designator:UnjfSpecification Data:80205-nas6708u18 professional/industrial association standardSheft Life:
Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Iron alloy 660Material Specification:Ams 5737 assn standard single material response and ams 5731 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseIntread Series Designator:UnifSpecification Data:80205-nas6708u18 professional/industrial association standardSheft Life:N/a

No

NSN 5306-01-365-7255

Shear Bolt - Page 2 of 2

Fiig: A003b0

