

View Online at <https://aerobasegroup.com/nsn/5306-01-365-7257>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.426 inches and 0.431 inches

Fastener Length:

Between 1.991 inches and 2.021 inches

Head Style:

Dished hexagon

Head Height:

Between 0.219 inches and 0.239 inches

Width Between Flats:

Between 0.678 inches and 0.690 inches

Grip Diameter:

Between 0.4672 inches and 0.4682 inches

Thread Diameter:

0.438 inches

Grip Length:

Between 1.302 inches and 1.322 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4340

Material Specification:

Mil-s-5000 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6607 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.