

View Online at <https://aerobasegroup.com/nsn/5306-01-365-8129>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

2.250 inches

Fastener Length:

Between 3.469 inches and 3.531 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.740 inches and 0.750 inches

Width Between Flats:

Between 0.745 inches and 0.753 inches

Extended Washer Diameter:

Between 1.107 inches and 1.125 inches

Extended Washer Thickness:

Between 0.318 inches and 0.338 inches

Thread Diameter:

0.750 inches

Grip Length:

Between 0.7406 inches and 0.7500 inches

Thread Qty Per Inch (tpi):

10

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 37.0 rockwell c

Material:

Steel comp 4140 or steel comp e4340 or steel comp 8640

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or astm a29 assn standard 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 ty2 cl3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.