

View Online at <https://aerobasegroup.com/nsn/5306-01-366-1112>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.537 inches and 1.781 inches

**Fastener Length:**

Between 1.719 inches and 1.781 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.616 inches and 0.625 inches

**Width Between Flats:**

Between 0.620 inches and 0.628 inches

**Extended Washer Diameter:**

Between 0.921 inches and 0.937 inches

**Extended Washer Thickness:**

Between 0.255 inches and 0.275 inches

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 0.6163 inches and 0.6250 inches

**Thready Qty Per Inch (tpi):**

17

**Hardness Rating:**

32.0 rockwell c and 37.0 rockwell c

**Material:**

Steel comp 4140 and steel comp e4340 or steel comp 8640

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or astm a29 assn standard 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 ty2 cl3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.