## NSN 5306-01-366-1112

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-366-1112
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.537 inches and 1.781 inches
Fastener Length:
Between 1.719 inches and 1.781 inches
Head Style:
Double hexagon extended washer
Head Height:
Between 0.616 inches and 0.625 inches
Width Between Flats:
Between 0.620 inches and 0.628 inches
Extended Washer Diameter:
Between 0.921 inches and 0.937 inches
Extended Washer Thickness:
Between 0.255 inches and 0.275 inches
Thread Diameter:
0.625 inches
Grip Length:
Between 0.6163 inches and 0.6250 inches
Thready Qty Per Inch (tpi):
17
Hardness Rating:
32.0 rockwell c and 37.0 rockwell c
Material:
Steel comp 4140 and steel comp e4340 or steel comp 8640
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or astm a29 assn standard
3rd material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 ty2 cl3 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5306-01-366-1112

Machine Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.