## NSN 5306-01-366-1123

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-366-1123

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.634 inches
Fastener Length:
Between 3.821 inches and 3.851 inches
Head Style:
Spline extended washer
Head Height:
Between 0.202 inches and 0.222 inches
Extended Washer Diameter:
Between 0.375 inches and 0.385 inches
Extended Washer Thickness:
Between 0.035 inches and 0.055 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Head Minor Diameter:
Between 0.360 inches and 0.375 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
14
Min. Tensile Strength (psi):
260000 pounds per square inch
Hardness Rating:
51.0 rockwell c and 54.0 rockwell c
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:

Mil-c-8837 type 2, cl 2 military specification single treatment response

Unjf

**Thread Series Designator:** 

## NSN 5306-01-366-1123

Shear Bolt - Page 2 of 2



N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.