

View Online at <https://aerobasegroup.com/nsn/5306-01-366-4526>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.425 inches

**Fastener Length:**

Between 1.847 inches and 1.877 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.156 inches and 0.171 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Shoulder Diameter:**

0.311 inches first shoulder and 0.312 inches first shoulder

**Shoulder Length:**

1.427 inches first shoulder and 1.447 inches first shoulder

**Thread Diameter:**

0.250 inches

**Thread Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Shoulder Shape:**

Round first shoulder

**Material:**

Iron alloy 660

**Material Specification:**

Ams5732 assn standard single material response

**Surface Treatment:**

Passivate headpassivate bearing surface of headchromium grippassivate threads

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response headqq-p-35 federal specification single treatment response bearing surface of headqq-c-320 cl2 federal specification 1st treatment response gripqq-p-35 federal specification single treatment response threads

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0