

View Online at <https://aerobasegroup.com/nsn/5306-01-367-9272>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.626 inches

Fastener Length:

Between 3.736 inches and 3.766 inches

Head Style:

Dished hexagon

Head Height:

Between 0.312 inches and 0.327 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Locking Feature:

Patch locking feature or pellet locking feature or strip locking feature

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 3.240 inches and 3.260 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Material:

Steel comp 4340 or steel comp 8740 plastic polyamide locking feature steel comp 4340 fastener or steel comp 8740 fastener

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response mil-s-5000 military specification 1st material response fastener or mil-s-6049 military specification 2nd material response fastener

Surface Treatment:

Cadmium and chromate cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response qq-p-416, ty2, cl2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas6210 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.