

View Online at <https://aerobasegroup.com/nsn/5306-01-367-9273>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.594 inches

Fastener Length:

Between 2.704 inches and 2.734 inches

Head Style:

Dished hexagon

Head Height:

Between 0.281 inches and 0.296 inches

Width Between Flats:

Between 0.865 inches and 0.877 inches

Locking Feature:

Patch locking feature or pellet locking feature or strip locking feature

Grip Diameter:

Between 0.5605 inches and 0.5615 inches

Thread Diameter:

0.562 inches

Grip Length:

Between 2.115 inches and 2.135 inches

Thread Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Material:

Steel comp 4340 or steel comp 8740 plastic polyamide locking feature steel comp 4340 fastener or steel comp 8740 fastener

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response mil-s-5000 military specification 1st material response fastener or mil-s-6049 military specification 2nd material response fastener

Surface Treatment:

Cadmium and chromate cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response qq-p-416, ty2, cl2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas6209 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.