## NSN 5306-01-367-9823

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-367-9823

**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.743 inches and 0.783 inches **Fastener Length:** Between 3.531 inches and 3.551 inches **Head Style:** Spline extended washer **Head Height:** Between 0.383 inches and 0.393 inches **Extended Washer Diameter:** Between 0.807 inches and 0.817 inches **Extended Washer Thickness:** Between 0.053 inches and 0.073 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Head Minor Diameter:** Between 0.485 inches and 0.500 inches **Thread Diameter:** 0.437 inches **Grip Length:** Between 2.768 inches and 2.788 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 46.0 rockwell c fastener and 50.0 rockwell c fastener Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837, type2, cl2 military specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5306-01-367-9823

Shear Bolt - Page 2 of 2



| Unit Of Mea | sure: |
|-------------|-------|
|-------------|-------|

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.