## NSN 5306-01-368-2546

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-368-2546



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.639 inches and 0.679 inches

#### Fastener Length:

Between 2.159 inches and 2.189 inches

#### Head Style:

Spline extended washer

#### **Head Height:**

Between 0.327 inches and 0.337 inches

#### **Extended Washer Diameter:**

Between 0.691 inches and 0.701 inches

#### **Extended Washer Thickness:**

Between 0.044 inches and 0.064 inches

#### **Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

#### Head Minor Diameter:

Between 0.423 inches and 0.438 inches

### Thread Diameter:

0.375 inches

Grip Length:

Between 1.490 inches and 1.510 inches

#### Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

46.0 rockwell c fastener and 50.0 rockwell c fastener

#### Material:

Steel comp h11

#### Material Specification:

Ams6487 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Mil-c-8837, type2, cl2 military specification single treatment response

#### Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5306-01-368-2546

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

