

View Online at <https://aerobasegroup.com/nsn/5306-01-368-2547>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.643 inches and 0.773 inches

Fastener Length:

Between 2.993 inches and 3.113 inches

Head Style:

Spline extended washer

Head Height:

Between 0.383 inches and 0.393 inches

Extended Washer Diameter:

Between 0.807 inches and 0.817 inches

Extended Washer Thickness:

Between 0.053 inches and 0.073 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Head Minor Diameter:

Between 0.485 inches and 0.500 inches

Thread Diameter:

0.437 inches

Grip Length:

Between 2.330 inches and 2.350 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

46.0 rockwell c fastener and 50.0 rockwell c fastener

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837, type2, cl2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.