NSN 5306-01-368-2547

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-368-2547

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.643 inches and 0.773 inches **Fastener Length:** Between 2.993 inches and 3.113 inches **Head Style:** Spline extended washer **Head Height:** Between 0.383 inches and 0.393 inches **Extended Washer Diameter:** Between 0.807 inches and 0.817 inches **Extended Washer Thickness:** Between 0.053 inches and 0.073 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Head Minor Diameter:** Between 0.485 inches and 0.500 inches **Thread Diameter:** 0.437 inches **Grip Length:** Between 2.330 inches and 2.350 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 46.0 rockwell c fastener and 50.0 rockwell c fastener Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837, type2, cl2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-368-2547

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.