NSN 5306-01-368-3707

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-368-3707								
Thread Class:								
3a								
Thread Direction:								
Right-hand								
Thread Length:								
Between 0.469 inches and 0.609 inches								
Fastener Length:								
Between 2.871 inches and 2.891 inches								
Head Style:								
Spline extended washer								
Head Height:								
Between 0.302 inches and 0.312 inches								
Extended Washer Diameter:								
Between 0.575 inches and 0.585 inches								
Extended Washer Thickness:								
Between 0.035 inches and 0.055 inches								
Grip Diameter:								
Between 0.3110 inches and 0.3120 inches								
Head Minor Diameter:								
Between 0.360 inches and 0.375 inches								
Thread Diameter:								
0.312 inches								
Grip Length:								
Between 2.282 inches and 2.302 inches								
Thready Qty Per Inch (tpi):								
24								
Min. Tensile Strength (psi):								
16000 pounds per square inch								
Hardness Rating:								
46.0 rockwell c fastener and 50.0 rockwell c fastener								
Material:								
Steel comp h11								
Material Specification:								
Ams6487 assn standard single material response								
Surface Treatment:								
Cadmium and chromate								
Surface Treatment Specification:								
Mil-c-8837, type2, cl2 military specification single treatment response								
Thread Series Designator:								
Unjf								
Shelf Life:								
N/a								

N/a

NSN 5306-01-368-3707

Shear Bolt - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.