NSN 5306-01-368-7316

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-368-7316

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.149 inches
Fastener Length:
Between 3.634 inches and 3.664 inches
Head Style:
Spline extended washer
Head Height:
0.600 inches
Extended Washer Diameter:
Between 1.384 inches and 1.394 inches
Extended Washer Thickness:
0.108 inches
Grip Diameter:
Between 0.7480 inches and 0.7490 inches
Head Minor Diameter:
Between 0.797 inches and 0.812 inches
Thread Diameter:
0.750 inches
Grip Length:
2.500 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
18000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Special Features:
Centerdrill in point end at manufacturer's option on dash number 12 and 14 sizes
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unif

Unjt

NSN 5306-01-368-7316

Shear Bolt - Page 2 of 2



	L -	11		ife	_
3	ne	п	_	пе	Ξ

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0