NSN 5306-01-368-7318

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-368-7318

| 3a |
|---|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.317 inches |
| Fastener Length: |
| Between 4.302 inches and 4.333 inches |
| Head Style: |
| Spline extended washer |
| Head Height: |
| 0.700 inches |
| Extended Washer Diameter: |
| Between 1.615 inches and 1.630 inches |
| Extended Washer Thickness: |
| 0.126 inches |
| Grip Diameter: |
| Between 0.8730 inches and 0.8740 inches |
| Head Minor Diameter: |
| 0.923 inches |
| Thread Diameter: |
| 0.875 inches |
| Grip Length: |
| 3.000 inches |
| Thready Qty Per Inch (tpi): |
| 14 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads |
| Special Features: |
| Centerdrill in point end at manufacturer's option on dash number 12 and 14 sizes |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams5662 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |

NSN 5306-01-368-7318

Shear Bolt - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0