NSN 5306-01-368-8043

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-368-8043

Tilleau Glass.
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.680 inches and 0.730 inches
Fastener Length:
Between 1.877 inches and 1.907 inches
Head Style:
Spline extended washer
Head Height:
Between 0.320 inches and 0.340 inches
Extended Washer Diameter:
Between 0.807 inches and 0.817 inches
Extended Washer Thickness:
Between 0.053 inches and 0.073 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.4365 inches and 0.4370 inches
Head Minor Diameter:
Head Minor Diameter: Between 0.340 inches and 0.485 inches
Between 0.340 inches and 0.485 inches
Between 0.340 inches and 0.485 inches Thread Diameter:
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches Grip Length:
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches Grip Length: Between 1.177 inches and 1.197 inches
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches Grip Length: Between 1.177 inches and 1.197 inches Hole Quantity:
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches Grip Length: Between 1.177 inches and 1.197 inches Hole Quantity:
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches Grip Length: Between 1.177 inches and 1.197 inches Hole Quantity: 4 Hole Type:
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches Grip Length: Between 1.177 inches and 1.197 inches Hole Quantity: 4 Hole Type: Drilled
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches Grip Length: Between 1.177 inches and 1.197 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi):
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches Grip Length: Between 1.177 inches and 1.197 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches Grip Length: Between 1.177 inches and 1.197 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi):
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches Grip Length: Between 1.177 inches and 1.197 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches Grip Length: Between 1.177 inches and 1.197 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style:
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches Grip Length: Between 1.177 inches and 1.197 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style: Spline
Between 0.340 inches and 0.485 inches Thread Diameter: 0.437 inches Grip Length: Between 1.177 inches and 1.197 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style: Spline Material:

Ams5629 federal specification single material response

Passivate

Surface Treatment:

NSN 5306-01-368-8043

Shear Bolt - Page 2 of 2



Surface Treatment Speci

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0