## NSN 5306-01-368-8044

Shear Bolt - Page 1 of 2

**Thread Class:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-368-8044

Thread Direction:	
Right-hand	
Thread Length:	
Between 0.680 inches and 0.730 inches	
Fastener Length:	
Between 2.065 inches and 2.095 inches	
Head Style:	
Spline extended washer	
Head Height:	
Between 0.310 inches and 0.350 inches	
Extended Washer Diameter:	
Between 0.807 inches and 0.817 inches	
Extended Washer Thickness:	
Between 0.053 inches and 0.073 inches	
Hole Diameter:	
Between 0.050 inches and 0.060 inches	
Grip Diameter:	
Between 0.4365 inches and 0.4370 inches	
Head Minor Diameter:	
Between 0.514 inches and 0.521 inches	
Thread Diameter:	
0.437 inches	
Grip Length:	
Between 1.365 inches and 1.385 inches	
Hole Quantity:	
4	
Hole Type:	
Drilled	
Features Provided:	
Dry film lubricant	
Thready Qty Per Inch (tpi):	
20	
Min. Tensile Strength (psi):	
220000 pounds per square inch	
Hole Configuration Style:	
Spline	
Material:	
Steel comp xm-13	
Material Specification:	
Ams5629 federal specification single material response	

## NSN 5306-01-368-8044

Shear Bolt - Page 2 of 2

A003b0



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: