

NSN 5306-01-368-8047 Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-368-8047 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.680 inches and 0.730 inches **Fastener Length:** Between 2.565 inches and 2.595 inches **Head Style:** Spline extended washer **Head Height:** Between 0.383 inches and 0.403 inches **Extended Washer Diameter:** Between 0.807 inches and 0.817 inches **Extended Washer Thickness:** 0.053 inches **Hole Diameter:** Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.4365 inches and 0.4370 inches **Head Minor Diameter:**

Between 0.514 inches and 0.521 inches

Thread Diameter:

0.438 inches

Grip Length:

Between 1.865 inches and 1.885 inches

Hole Quantity:

Hole Type:

Drilled

Features Provided:

Dry film lubricant

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Spline

Material:

Steel comp xm-13

Material Specification:

As8879 assn standard single material response

NSN 5306-01-368-8047

Shear Bolt - Page 2 of 2

A003b0



Surface Treatment:
Passivate
Surface Treatment Specification:
Ams2700 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: