## NSN 5306-01-368-8048

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-368-8048



**Thread Class:** 3a

**Thread Direction:** 

**Right-hand** 

Thread Length:

Between 0.443 inches and 0.493 inches

Fastener Length:

Between 1.765 inches and 1.795 inches

Head Style:

Spline extended washer

Head Height:

Between 0.204 inches and 0.224 inches

## **Extended Washer Diameter:**

Between 0.460 inches and 0.470 inches

## **Extended Washer Thickness:**

Between 0.026 inches and 0.046 inches

## Hole Diameter:

Between 0.032 inches and 0.042 inches

## **Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

## Head Minor Diameter:

Between 0.297 inches and 0.312 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 1.302 inches and 1.322 inches

Hole Quantity:

4

Hole Type:

Drilled

## **Features Provided:**

Dry film lubricant

Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

220000 pounds per square inch

## Hole Configuration Style:

Spline

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

# NSN 5306-01-368-8048

Shear Bolt - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0