

View Online at <https://aerobasegroup.com/nsn/5306-01-371-1705>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.705 inches

**Fastener Length:**

Between 1.485 inches and 1.515 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.383 inches and 0.403 inches

**Extended Washer Diameter:**

Between 0.807 inches and 0.817 inches

**Extended Washer Thickness:**

Between 0.053 inches and 0.073 inches

**Grip Diameter:**

Between 0.4365 inches and 0.4370 inches

**Head Minor Diameter:**

0.514 inches

**Thread Diameter:**

0.437 inches

**Grip Length:**

Between 0.770 inches and 0.790 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

22000 pounds per square inch

**Surface Finish:**

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0