## NSN 5306-01-371-1705

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-371-1705

3
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.705 inches
Fastener Length:
Between 1.485 inches and 1.515 inches
Head Style:
Spline extended washer
Head Height:
Between 0.383 inches and 0.403 inches
Extended Washer Diameter:
Between 0.807 inches and 0.817 inches
Extended Washer Thickness:
Between 0.053 inches and 0.073 inches
Grip Diameter:
Between 0.4365 inches and 0.4370 inches
Head Minor Diameter:
0.514 inches
Thread Diameter:
0.437 inches
Grip Length:
Between 0.770 inches and 0.790 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
22000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-371-1705

Shear Bolt - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0