

View Online at <https://aerobasegroup.com/nsn/5306-01-371-5679>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.648 inches

**Fastener Length:**

Between 4.161 inches and 4.181 inches

**Head Style:**

Crowned hexagon

**Head Height:**

Between 0.313 inches and 0.328 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Grip Diameter:**

Between 0.6232 inches and 0.6241 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 3.312 inches and 3.328 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 41.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.051 inches first hole

**Surface Finish:**

63.0 microinches bearing surface of head 63.0 microinches grip

**Special Features:**

With retaining ring on shank

**Material:**

Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 8740 fastener or steel comp 4130 fastener or steel comp 6150 fastener

**Material Specification:**

Mil-s-5000 military specification 1st material response fastener or mil-s-5626 military specification 2nd material response fastener or mil-s-6049 military specification 3rd material response fastener or mil-s-6758 military specification 4th material response fastener or mil-s-8503 military specification 5th material response fastener

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.