## NSN 5306-01-371-8453

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-371-8453

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.492 inches
Fastener Length:
5.137 inches
Head Style:
Double hexagon w/hole
Head Height:
0.300 inches
Width Between Flats:
0.312 inches
Extended Washer Diameter:
Between 0.428 inches and 0.438 inches
Extended Washer Thickness:
0.069 inches
Hole Diameter:
Between 0.032 inches and 0.042 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 4.615 inches and 4.635 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
20.0 manipus II a good 42.0 manipus II a

39.0 rockwell c and 43.0 rockwell c

**Hole Configuration Style:** 

Double hexagon longitudinal hole

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches threads

Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150

## NSN 5306-01-371-8453

Shear Bolt - Page 2 of 2

Fiig: A003b0



Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No