

View Online at <https://aerobasegroup.com/nsn/5306-01-372-4033>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.310 inches

**Fastener Length:**

4.710 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.500 inches and 0.515 inches

**Width Between Flats:**

Between 1.427 inches and 1.440 inches

**Grip Diameter:**

Between 0.9985 inches and 0.9990 inches

**End Application:**

C17a serd 110056

**Thread Diameter:**

1.000 inches

**Grip Length:**

3.120 inches

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Special Features:**

Altered item made from nas6716u54: drilled shank threaded end to shank hole 0.254 to 0.274 inch: hole diameter 0.110 to 0.140 inch

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard 1st material response and ams 5737 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0