

View Online at <https://aerobasegroup.com/nsn/5306-01-372-4034>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.570 inches

Fastener Length:

3.450 inches

Head Style:

Dished hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

End Application:

C17a serd 110056

Thread Diameter:

0.375 inches

Grip Length:

2.880 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Special Features:

Altered item made from nas6706u46: used on adapter, pylon, instl-transp: drilled shank threaded end to shank hole 0.120 inch: hole diameter 0.062 to 0.065 inch

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard 1st material response or ams 5737 assn standard 2nd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0