

View Online at <https://aerobasegroup.com/nsn/5306-01-374-0383>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.659 inches

Fastener Length:

Between 1.294 inches and 1.324 inches

Head Style:

Spline extended washer

Head Height:

0.070 inches

Extended Washer Diameter:

Between 0.691 inches and 0.701 inches

Extended Washer Thickness:

Between 0.044 inches and 0.064 inches

Shoulder Diameter:

0.3735 inches first shoulder and 0.3745 inches first shoulder

Shoulder Length:

0.430 inches first shoulder

Hole Diameter:

Between 0.060 inches and 0.070 inches

Head Minor Diameter:

Between 0.423 inches and 0.438 inches

Thread Diameter:

0.375 inches

Hole Quantity:

8

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

16720 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Shoulder Shape:

Round first shoulder

Special Features:

220000 ksi fut at 800 degrees fahrenheit

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response or ams 5663 assn standard single material response

Surface Treatment:

Passivate or cadmium and chromate

Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response or qq-p-416, type 2, class 2 federal specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0