

View Online at <https://aerobasegroup.com/nsn/5306-01-374-0383>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.659 inches

**Fastener Length:**

Between 1.294 inches and 1.324 inches

**Head Style:**

Spline extended washer

**Head Height:**

0.070 inches

**Extended Washer Diameter:**

Between 0.691 inches and 0.701 inches

**Extended Washer Thickness:**

Between 0.044 inches and 0.064 inches

**Shoulder Diameter:**

0.3735 inches first shoulder and 0.3745 inches first shoulder

**Shoulder Length:**

0.430 inches first shoulder

**Hole Diameter:**

Between 0.060 inches and 0.070 inches

**Head Minor Diameter:**

Between 0.423 inches and 0.438 inches

**Thread Diameter:**

0.375 inches

**Hole Quantity:**

8

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

16720 pounds per square inch

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Shoulder Shape:**

Round first shoulder

**Special Features:**

220000 ksi fut at 800 degrees fahrenheit

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response or ams 5663 assn standard single material response

**Surface Treatment:**

Passivate or cadmium and chromate

**Surface Treatment Specification:**

Qq-p-35 federal specification 1st treatment response or qq-p-416, type 2, class 2 federal specification 2nd treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0