NSN 5306-01-374-9824

Close Tolerance Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-374-9824

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.725 inches |
| Fastener Length: |
| Between 2.146 inches and 2.193 inches |
| Head Style: |
| Double hexagon |
| Head Height: |
| Between 0.318 inches and 0.338 inches |
| Width Between Flats: |
| 0.877 inches |
| Grip Diameter: |
| Between 0.5610 inches and 0.5615 inches |
| Thread Diameter: |
| 0.562 inches |
| Grip Length: |
| Between 1.427 inches and 1.447 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Material: |
| Steel comp xm-13 |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |
| |