

View Online at <https://aerobasegroup.com/nsn/5306-01-375-1214>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.425 inches

Fastener Length:

Between 1.972 inches and 2.002 inches

Head Style:

Dished hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.429 inches and 0.439 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

Between 1.552 inches and 1.572 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.809 inches first hole

Surface Finish:

32.0 microinches first hole 32.0 microinches grip 32.0 microinches threads

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6704 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0