NSN 5306-01-375-7129



Shoulder Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-375-7129 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.184 inches **Fastener Length:** Between 5.549 inches and 5.560 inches **Head Style:** Dished hexagon **Head Height:** Between 0.500 inches and 0.515 inches Width Between Flats: Between 1.427 inches and 1.440 inches **Shoulder Diameter:** 0.998 inches first shoulder and 0.999 inches first shoulder **Shoulder Length:** 4.365 inches first shoulder and 4.385 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.141 inches first hole and 0.151 inches first hole **Thread Diameter:** 0.875 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 95000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 5.365 inches first hole and 5.419 inches first hole **Shoulder Shape:** Round first shoulder Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5306-01-375-7129 Shoulder Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

Demilitarization:

No

Fiig:

A003b0