NSN 5306-01-376-9485

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-376-9485

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.786 inches |
| Fastener Length: |
| 3.099 inches |
| Head Style: |
| Spline extended washer |
| Head Height: |
| Between 0.327 inches and 0.347 inches |
| Extended Washer Diameter: |
| Between 0.691 inches and 0.701 inches |
| Extended Washer Thickness: |
| Between 0.044 inches and 0.064 inches |
| Grip Diameter: |
| Between 0.3735 inches and 0.3745 inches |
| Head Minor Diameter: |
| Between 0.423 inches and 0.438 inches |
| Thread Diameter: |
| 0.375 inches |
| Grip Length: |
| 2.313 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams 5662 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5306-01-376-9485

Shear Bolt - Page 2 of 2



| Demi | | | |
|------|--|--|--|
| | | | |
| | | | |

No

Fiig:

A003b0