NSN 5306-01-377-3660

Shear Bolt - Page 1 of 2





- Thread Class: 3a
- Thread Direction:

Right-hand

Thread Length:

0.763 inches

Fastener Length:

Between 2.408 inches and 2.428 inches

Head Style:

Spline extended washer

Head Height:

Between 0.383 inches and 0.403 inches

Extended Washer Diameter:

Between 0.807 inches and 0.817 inches

Extended Washer Thickness:

Between 0.053 inches and 0.073 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Head Minor Diameter:

Between 0.485 inches and 0.500 inches

Thread Diameter:

0.437 inches

Grip Length:

Between 1.615 inches and 1.635 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response or ams 5663 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5306-01-377-3660

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

