

View Online at <https://aerobasegroup.com/nsn/5306-01-378-4320>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.439 inches

Fastener Length:

Between 7.424 inches and 7.454 inches

Head Style:

Double hexagon extended washer

Head Height:

0.806 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Extended Washer Diameter:

Between 1.415 inches and 1.425 inches

Extended Washer Thickness:

0.152 inches

Grip Diameter:

Between 0.748 inches and 0.749 inches

End Application:

F-111 all

Thread Diameter:

0.750 inches

Grip Length:

6.000 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

51.0 rockwell c fastener and 54.0 rockwell c fastener

Material:

Steel comp h11

Material Specification:

Ams6485 assn standard 1st material response or ams 6487 assn standard 2nd material response

Surface Treatment:

Cadmium or nickel

Surface Treatment Specification:

Mil-c-8837, type ii, class 3, type ii, class 2 military specification single treatment response or ams 2416 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.