

View Online at <https://aerobasegroup.com/nsn/5306-01-378-4320>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.439 inches

**Fastener Length:**

Between 7.424 inches and 7.454 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

0.806 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Extended Washer Diameter:**

Between 1.415 inches and 1.425 inches

**Extended Washer Thickness:**

0.152 inches

**Grip Diameter:**

Between 0.748 inches and 0.749 inches

**End Application:**

F-111 all

**Thread Diameter:**

0.750 inches

**Grip Length:**

6.000 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hardness Rating:**

51.0 rockwell c fastener and 54.0 rockwell c fastener

**Material:**

Steel comp h11

**Material Specification:**

Ams6485 assn standard 1st material response or ams 6487 assn standard 2nd material response

**Surface Treatment:**

Cadmium or nickel

**Surface Treatment Specification:**

Mil-c-8837, type ii, class 3, type ii, class 2 military specification single treatment response or ams 2416 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.