-379-8398 ICN EDAG Ω1



roup.com/nsn/5306-01-379-8398

| NSN 5306-01-379-83 Shear Bolt - Page 1 of 1 |
|--|
| View Online at https://aerobasegroup.com/r |
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.345 inches |
| Fastener Length: |
| Between 1.392 inches and 1.422 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.110 inches and 0.125 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Grip Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 1.052 inches and 1.072 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| |

32.0 microinches threads

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response point or ams4967 assn standard single material response point

Surface Treatment:

Aluminum

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0