NSN 5306-01-382-6022

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-382-6022
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.875 inches and 0.935 inches
Fastener Length:
1.125 inches
Head Style:
Double hexagon extended washer
Head Height:
0.338 inches
Width Between Flats:
0.375 inches
Extended Washer Diameter:
0.500 inches
Extended Washer Thickness:
Between 0.070 inches and 0.080 inches
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
165000 pounds per square inch
Criticality Code Justification:
Thsd
Surface Finish:
32.0 microinches grip
Special Features:
Thread is a safety critical thread in accordance with mil-s-8879 under application category safety critical. Apply one coat of mil-p-23377,
type 1, cl1 or 3 and two top coats 0f mil-c-46168, color code 33538 per fed-std-595 to top of head
Material:
Nickel alloy
Material Specification:
Ams 5708 assn standard single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5306-01-382-6022 Machine Bolt - Page 2 of 2



Fiig:

A003b0