NSN 5306-01-382-6024

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-382-6024	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.752 inches	
Fastener Length:	
1.625 inches	
Head Style:	
Double hexagon extended washer	
Head Height:	
0.260 inches	
Width Between Flats:	
0.250 inches	
Extended Washer Diameter:	
0.375 inches	
Extended Washer Thickness:	
0.040 inches	
Hole Diameter:	
0.047 inches	
Thread Diameter:	
0.190 inches	
Hole Quantity:	
4	
Hole Type:	
Drilled	
Thready Qty Per Inch (tpi):	
32	
Min. Tensile Strength (psi):	
130000 pounds per square inch	
Minimum Yield Strength:	
85000 pounds per square inch	
Hole Configuration Style:	
Double hexagon longitudinal hole	
Criticality Code Justification:	
Thsd	
Surface Finish:	
32.0 microinches grip	
Special Features:	
Thread is a safety critical thread in accordance with mil-s-8879 under apllication category safety critical. Apply one coat of mil-p-23377, type	е
1. cl 1 or 3 and two top coats of mil-c-46168, color code 33538 per fed-std-595 to top of head	

Material:

Iron alloy 660

NSN 5306-01-382-6024

Machine Bolt - Page 2 of 2



N	/lat	۵r	ial	Sp	200	·ifi	Ca	tic	۱n	٠
•	naı	C.	ıuı	~	,,,,	••••	vu		<i>,</i> ,,,	

Ams 5731 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0