## NSN 5306-01-382-7478

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-382-7478 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.435 inches **Fastener Length:** Between 0.830 inches and 0.860 inches **Head Style:** Spline extended washer **Head Height:** Between 0.240 inches and 0.260 inches **Extended Washer Diameter:** Between 0.460 inches and 0.470 inches **Extended Washer Thickness:** Between 0.026 inches and 0.046 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Head Minor Diameter:** Between 0.236 inches and 0.280 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c Material: Steel comp 4140 or steel comp 4340 or steel comp 6150 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification all treatment responses **Thread Series Designator:** Unjf Shelf Life:

**Unit Of Measure:** 

N/a

## NSN 5306-01-382-7478

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0