# NSN 5306-01-382-9981

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-382-9981

## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.875 inches

## Fastener Length:

1.250 inches

#### **Head Style:**

Double hexagon w/hole

#### **Head Height:**

0.375 inches

## Width Between Flats:

0.375 inches

#### **Extended Washer Diameter:**

0.500 inches

## **Extended Washer Thickness:**

Between 0.070 inches and 0.080 inches

Hole Diameter:

0.070 inches

## **Thread Diameter:**

0.312 inches

#### Hole Quantity:

4

## Hole Type:

Drilled

# Thready Qty Per Inch (tpi):

24

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

# Hole Configuration Style:

Double hexagon longitudinal hole

# Criticality Code Justification:

Thsd

# Surface Finish:

63.0 microinches grip

# **Special Features:**

Nthread is safety critical per mil-s-7742 under application category safety critical. Apply one coat of mil-p-23377, type 1, cl 1 or 3 and two top coats of mil-c-46168, color code 33538 per fed-std-595 to top of head

## Material:

Steel comp 8740

## Material Specification:

Ams 6322 assn standard single material response

# NSN 5306-01-382-9981

Machine Bolt - Page 2 of 2



Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0