

View Online at <https://aerobasegroup.com/nsn/5306-01-383-9940>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.036 inches

Fastener Length:

1.681 inches

Head Style:

Double hexagon extended washer

Head Height:

0.711 inches

Width Between Flats:

0.812 inches

Extended Washer Diameter:

Between 1.220 inches and 1.230 inches

Extended Washer Thickness:

0.178 inches

Hole Diameter:

Between 0.045 inches and 0.060 inches

Grip Diameter:

Between 0.797 inches and 0.812 inches

Thread Diameter:

0.750 inches

Grip Length:

Between 0.615 inches and 0.635 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

180000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Material:

Steel comp 4140

Material Specification:

Mil-s-5626 4140 military specification single material response

Surface Treatment:

Phosphate zinc

Surface Treatment Specification:

Mil-std-171 5.1.1 military standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.