

View Online at <https://aerobasegroup.com/nsn/5306-01-383-9940>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.036 inches

**Fastener Length:**

1.681 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

0.711 inches

**Width Between Flats:**

0.812 inches

**Extended Washer Diameter:**

Between 1.220 inches and 1.230 inches

**Extended Washer Thickness:**

0.178 inches

**Hole Diameter:**

Between 0.045 inches and 0.060 inches

**Grip Diameter:**

Between 0.797 inches and 0.812 inches

**Thread Diameter:**

0.750 inches

**Grip Length:**

Between 0.615 inches and 0.635 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626 4140 military specification single material response

**Surface Treatment:**

Phosphate zinc

**Surface Treatment Specification:**

Mil-std-171 5.1.1 military standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.